



Nordic Wabi Sabi Fiberglass Pendant Light

PENDANT LIGHT | SKU NOT PROVIDED

MATERIAL

Fiberglass

LIGHT SOURCE

See product label

VOLTAGE

110V-240V

INSTALLATION

Hardwired ceiling mount

SPECIFICATIONS

MATERIAL	Fiberglass
VOLTAGE	110V-240V
COLOR TEMPERATURE	3000K warm light (others available upon request)
INSTALLATION	Hardwired ceiling mount
CORD / SUSPENSION	50-150 cm
ILLUMINATION AREA	15m2-30m2

AVAILABLE CONFIGURATIONS

White / D20cm; White / D30cm; White / D40cm; White / D50cm; White / D60cm; White / D80cm; Dark Grey / D20cm; Dark Grey / D30cm; plus 10 more

INSTALLATION OVERVIEW

- 1

Confirm that the mounting location and junction box can support the fixture.
- 2

A qualified licensed electrician should isolate power and install the supplied mounting hardware.
- 3

Set the suspension length before the canopy is secured, following the components supplied with the fixture.
- 4

Use only the lamp type and electrical rating shown on the product label.

SAFETY

Disconnect power before electrical work. Hardwired fixtures must be installed by a qualified licensed electrician in accordance with local electrical codes. Product components and ratings can vary by option; confirm all values on the product label and supplied instructions before installation.

CARE

Switch off and allow the fixture to cool. Dust with a soft, dry cloth. Do not use abrasives, solvents, or excess moisture. Natural stone, glass, ceramic, wood, and hand-finished metal may show normal variation.